

CLAIMS

1. A liquid ejection head comprising:

a liquid path;

5 an ejection outlet forming member which constitutes a part of a wall of the liquid and which forms an ejection outlet for ejecting a droplet of liquid;

a heat generating element, provided at a position opposing to said ejection outlet of the wall of said liquid flow path, for generating a bubble in the liquid by application of heat to the liquid;

a restrictor portion, provided at a recessed portion of said ejection outlet, wherein said recessed portion is recessed from a plane in which said ejection outlet is formed, wherein the liquid forms a meniscus and is retained in said ejection outlet such that said restrictor portion is within the liquid,

wherein an area S_o of an opening of said restrictor portion and a surface S_h of said heat generating element satisfy $S_o \leq S_h$.

2. A liquid ejection head comprising:

a liquid path;

25 an ejection outlet forming member which constitutes a part of a wall of the liquid and which forms an ejection outlet for ejecting a droplet of

liquid;

an energy generating element, provided at a position opposing to said ejection outlet of the wall of said liquid flow path, for generating ejection
5 energy to be applied to the liquid;

a restrictor portion, provided at a recessed portion of said ejection outlet, wherein said recessed portion is recessed from a plane in which said ejection outlet is formed, wherein the liquid forms a
10 meniscus and is retained in said ejection outlet such that said restrictor portion is within the liquid,

wherein a thickness c of said restrictor portion and a height e of said liquid path measured in a direction in which said ejection outlet and said
15 energy generating element are faced to each other, satisfy $c \leq e$.

3. A liquid ejection head according to Claim 2, wherein said energy generating element is a heat
20 generating element.

4. A liquid ejection head according to Claim 2, wherein an area S_o of an opening of said restrictor portion and a surface S_h of said heat generating
25 element satisfy $S_o \leq S_h$.

5. A liquid ejection head comprising:

a liquid path;

an ejection outlet forming member which constitutes a part of a wall of the liquid and which forms an ejection outlet for ejecting a droplet of liquid;

an energy generating element, provided at a position opposing to said ejection outlet of the wall of said liquid flow path, for generating ejection energy to be applied to the liquid;

a restrictor portion, provided at a recessed portion of said ejection outlet, wherein said recessed portion is recessed from a plane in which said ejection outlet is formed, wherein the liquid forms a meniscus and is retained in said ejection outlet such that said restrictor portion is within the liquid,

wherein a thickness c of said restrictor portion and a

thickness d of said ejection outlet forming member measured between a plane in which said ejection outlet is formed and said restrictor portion, satisfy $c \leq d$.

6. A liquid ejection head according to Claim 1, 2 or 5, wherein said restrictor portion is disposed in a middle in a direction of a thickness of said ejection outlet forming member.

7. A liquid ejection head according to Claim 1, 2 or 5, wherein a diameter of the opening of said restrictor portion changes along a direction of ejection of the liquid through said ejection outlet.

5

8. A liquid ejection head according to Claim 1, 2 or 5, wherein said restrictor portion has the opening including a plurality of fine bores.

10

9. A liquid ejection head according to Claim 1, 2 or 5, wherein the liquid is recording liquid usable with ink jet recording.

15

10. A liquid ejection head according to Claim 1, 2 or 5, wherein the liquid is medicine to be inhaled into a lung.

20

11. A liquid ejection head according to Claim 5, wherein an area S_o of an opening of said restrictor portion and a surface S_h of said heat generating element satisfy $S_o \leq S_h$.

25

12. A liquid ejection head according to Claim 5 or 11, wherein a height e of said liquid path measured in a direction in which said ejection outlet and said energy generating element are faced to each other, satisfy $c \leq e$.